




## MONTO® Single-section leaning rung ladder Sibilo®

A lightweight aluminium leaning ladder suitable for a wide range of uses.

- + Rungs are profiled on all sides
- + Longlasting 32-times flanged rung/side rail connections
- + Large dimensioned side rails
- + Slip-resistant foot plugs or -caps (SafetyCap)
- + Supplied with extra stabiliser for even greater safety from 12 rungs and above

SafetyCap



| Number of rungs          |                    |                 | 6      | 9      | 12     | 15     | 18     |
|--------------------------|--------------------|-----------------|--------|--------|--------|--------|--------|
| 1                        |                    | A up to approx. | m 2.80 | 3.60   | 4.40   | 5.25   | 6.05   |
|                          |                    | B approx.       | m 0.80 | 1.60   | 2.40   | 3.25   | 4.05   |
| 2                        |                    | C approx.       | m 1.90 | 2.70   | 3.55   | 4.40   | 5.25   |
|                          |                    | D approx.       | m 1.80 | 2.60   | 3.40   | 4.25   | 5.05   |
| Stabiliser width approx. |                    | m               | –      | –      | 0.80   | 0.80   | 0.90   |
| Product weight approx.   |                    | kg              | 2.8    | 4.3    | 6.5    | 8.0    | 9.5    |
|                          | Width (B) approx.  | m               | 0.35   | 0.35   | 0.35   | 0.35   | 0.35   |
|                          | Depth (T) approx.  | m               | 0.05   | 0.05   | 0.05   | 0.05   | 0.05   |
|                          | Length (L) approx. | m               | 1.90   | 2.70   | 3.55   | 4.40   | 5.25   |
| Art.-No.                 |                    |                 | 121387 | 120519 | 129109 | 129123 | 129154 |

| Combi System |      |      |     |      |     |       |      |  |
|--------------|------|------|-----|------|-----|-------|------|--|
|              | 6–18 | 6–18 | 6–9 | 6–18 | 6–9 | 12–18 | 6–18 |  |
| Page 96      | ①    | ②    | ③   | ④    | ⑤   | ⑥     | ⑧    |  |



Sizes 6–9 rungs can be used without stabiliser

Sizes 12–18 rungs can only be used with stabiliser according to DIN EN 131-1:2015.