



The pictures may differ in color from the original product.

## Yukon

- ◇ Natural wood look
- ◇ Dimensionally stable and water-resistant
- ◇ Can be laid over large areas (up to 400 m<sup>2</sup>)
- ◇ Phthalates free
- ◇ Only 3,8 mm installation height
- ◇ Format 1220 x 228 mm
- ◇ Wear layer 0,5 mm
- ◇ Box content 10 planks = 2,782 m<sup>2</sup>
- ◇ Simple, floating installation
- ◇ Uniclic connection
- ◇ Low emission (certified A+)
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Utilisation class 23/32

### Please note before laying:

- Quantity required +10% of the surface area
- Subfloor clean, hard, even, stable and firm
- Level out any unevenness (max. 3 mm per 1,2 m)
- Lay the planks horizontally in the room for at least 24 hours to acclimatise!
- **Important:** Room temperature = floor temperature during installation
- User temperature 15°C to 60°C

### Note the following when laying:

- If an underlay mat is required: Use a pressure-resistant mat approved exclusively for vinyl/SPC (at least 500 kPa up to 1,5 mm, non-adhesive)
- On linoleum and wooden boards: Is a underlay mat or a 0,2 mm PE construction film for decoupling absolutely necessary!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8-10 mm
- A maximum area of 20 x 20 m (400 m<sup>2</sup>) can be laid without expansion joints



Article No.	Facido No.	Description	EAN	Pack/Pallet
32184226	106101994	RIGID SPC, Yukon, 3,8/0,5 mm	7640370941997	33