

HARVIA TOP STEEL

HM600400BX

The Harvia Top Steel, a favourite among Finns, is a traditional wall-mounted heater in which price and quality meet in a manner that is sure to warm the bather.

Advantages

- Popular wall-mounted heater
- Heats up the sauna quickly
- Control switches on the side can be placed on the left or right side



Features

Main material : Steel

H x W x D : 650.0 x 410.0 x 290.0 mm

Net weight (kg) : 12.5

Installation location : Wall

| ID | GTIN | Output (kW) | Sauna room size min - max m3 |
|------------|---------------|-------------|------------------------------|
| HM600400BX | 6417659022101 | 6 kW | 5.0-8.0 |


Related products



HSW5



HSW5L



HSW1

Spare parts

| Product | ID | Pcs |
|------------------------------------|-----------|-----|
| Heating element 2000W/230V | ZSK-700 | 1 |
| Gasket plate for heating element | ZSK-810 | |
| End-piece of connection box M | ZST-350 | |
| Slot-headed screw Din 7985 M5*10 S | ZSK-620 | |
| Furnace grate for KIP | ZSK-80 | |
| Gasket for heating element | ZSK-800 | |
| Montage plate Termonator | ZST-120 | |
| Connection box Termonator | ZST-140 | |
| Packing box for Termonator Eco | ZST-255 | |
| Harvia mark with sticker | ZH1-180 | |
| | ZST-5 | |
| Heating element 2000W 230V | SPZSK-700 | |

Technical details

| Technical data | Type / attribute | HM600400BX |
|------------------------------------|--|------------|
| Technical data | Color | Black |
| | Power output | 6 kW |
| | Stone amount (kg) | 20 |
| Dimensions | Product width | 410 |
| | Product height | 650 |
| | Product depth (mm) | 290 |
| | Net weight (kg) | 12.5 |
| | Gross weight | 13.6 |
| | Package width | 425 |
| | Package height | 665 |
| Safety and installation dimensions | Package depth | 325 |
| | Safety distance front (non-combustible materials) | 30 |
| | Safety distance side (non-combustible materials) | 50 |
| | Safety distance (Ceiling) | 1100 |
| | Room min. height(depends on connections and therefore from output, star/delta) | 1900 |
| | Installation opening height | 1900 |