



tesa® Draad shower grab bar, self-adhesive, chromed metal

BNR 40229

It's simple to put up the self-adhesive tesa® Draad shower grab bar without drilling. There's no damage to walls or tiles. The bar has an attractive rounded design. It can be swiftly removed at any time, without a trace left behind. Reuse is also easy, only requiring a new adapter BK164-2.

Features

- Bath grab bar with patented tesa® Power.Kit fastening technology
- Stainless steel, chromed, guaranteed rustproof, round wall plates
- Secure hold and very high strength – withstands a load of up to 130 kg (tested to ISO17966:2016)
- Removable, no damage to the surface, reusable with the fastening adapter BK 164-2
- Easy and clean fitting without drilling
- Suitable for even, glazed tiles with only occasional splash water – splash-proof according to IPX4
- Not suitable for fitting under water and surfaces other than glazed tiles
- Dimensions: 60 mm x 317 mm x 75 mm
- The product life span is 5 years when used properly

Product Properties

- | | | | |
|---------------------------|------------|----------------------|-------|
| • Curing time | 24 hour(s) | • Suitable surfaces | Tiles |
| • Applicationfield | Bathroom | • Reusable | yes |
| • UV-resistant | yes | • Waterproof | yes |
| • Water resistant | yes | • Hook shape | Round |
| • Humidity resistant | yes | • Batteries required | no |
| • Resistance to chemicals | No | • Batteries included | no |
| • Solvent free | yes | | |

Technical Data

- | | | | |
|---------------|---------------|--------------------------|-------------------------|
| • Area of use | Indoor | • Residue-free removable | yes |
| • Material | Chromed Steel | • Type of adhesive | Silane modified polymer |

tesa[®] Draad shower grab bar, self-adhesive, chromed metal

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=NaN>