

BATTERY

- Powerful 20 V / 2.0 Ah (SBP2.0) or 20 V / 4.0 Ah (SBP4.0) Lithium-ion battery
- Universal use – one battery for the entire Scheppach IXES 20 Volt series
- The remaining battery capacity can be read conveniently on the 3-level LED display
- Individual cell management protects from overheating as well as excess voltage and ensures uniform charging and discharging of the cells
- Extended battery life and run time, thanks to the minimised risk of excessive charging and deep discharge
- Work protecting resources by using just one battery system
- Charging time approx. 35 to 60 mins (SBP2.0) / 60 to 120 mins (SBP4.0) (depending on charger)
- Low weight ensures comfortable operation
- High impact resistance and pleasant haptics, thanks to rubberised housing
- Housing protected from dust and corrosion

PRODUCT DETAILS

Charging time
approx. 35 – 60 mins (SBP2.0)
approx. 60 – 120 mins (SBP4.0)

Long service life



LED indicator light



20 V



Part of the battery platform



Rubberised housing

Housing protected from dust and corrosion



LED indicator light

High impact resistance

Charger available separately

SPECIFICATIONS

	SBP2.0	SBP4.0
Dimensions L x W x H	125 x 80 x 50 mm	125 x 80 x 70 mm
Battery capacity	2.0 Ah	4.0 Ah
Battery tension	20 V	20 V

LOGISTICAL DATA

	SBP2.0	SBP4.0
Weight net / gross	0.4 / 0.5 kg	0.7 / 0.8 kg
Packaging dimensions	138 x 85 x 62 mm	140 x 85 x 82 mm
Article number	7909201708	7909201709
Barcode	4014915236481	4014915236504
20 Container	20,700 pcs	16,260 pcs