in accordance with manual of tests and criteria

7. revised edition, amendment 1, subsection 38.3.5

N/A = Not Applicable

4 11 (5				M/A = Not Applicable
	escription of battery			
SBP4.0	0			
1a. Name/D	escription of the cells inside t	ne ballery		
5INR1	9/66		· · ·	
	nary of the cells inside the batt that the UN 38.3 test summar	ery must either be presented or und y for the cells is available.	der checkpoint 9 and 9a it	must
2. Manufac	turer of battery			
Name	Scheppach GmbH			
Address	Günzburger Str. 69,	89335 Ichenhausen		
Phone	08223/ 4002 0			
Email	info@scheppach.co	m		
Website	www.scheppach.coi	n		
				<u> </u>
2a. Manufac	turer of the equipment (if the b	attery is contained in equipment)		
Name	W .			
Address				
Phone				
Email				
Website				
3. Test labo	oratory of battery			
Name	Shanghai Research	Institute of Chemical Indus	stry Testing Co., Ltd	
Address	West entrance, No.	345 East Yun Ling Road, S	Shanghai	
Phone	86-21-31765555			· · · · · · · · · · · · · · · · · · ·
Email	battery@ghs.cn		<u></u>	
Website	http://www.ghs.cn			
4. ID numb	per and date			
Unique test report identification number		1123080593	Date of test report	28.08.2023

Page 1/4

Version 1/2023

© This form was provided by www.lithium-battery-service.com



in accordance with manual of tests and criteria 7. revised edition, amendment 1, subsection 38.3.5

Name/Description of battery (taken from field 1)

SBP4.0

DESCRIPTION OF BATTERY

 Mark the type of battery with an "•" Note: Single cell batteries (1S1P) are treated as cells, i.e. 	using this logistic information form is correct.
Lithium ion battery	Lithium metal battery
Lithium hybrid battery	
6. Parameters	
Weight of the battery in gram (g) or kilogram (kg)	g
Lithium ion: Nominal energy in Watt-hours (Wh) or kilo Wat	t-hours (kWh) 80 Wh
Lithium metal: Lithium metal content in gram (g) or kilogram	n (kg) g
Lithium hybrid: Nominal energy in Watt-hours (Wh) or kilo \alpha and lithium metal content in gram (g) or kilogram (kg)	Vatt-hours (kWh) g
7. Physical description of battery	
Rechargeable Li-ion	
8. Model numbers	
7909201709	

TESTS AND RESULTS

9. List of tests conducted and results - Mark N/A, pass or fail with an "•"		pass
T1 - Altitude simulation		√
T2 - Thermal Test		√
T3 - Vibration		√
T4 - Shock		1
T5 - External Short Circuit		√
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm See check point 1a and 9a.		✓
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm. See check point 1a and 9a.		✓
T7 - Overcharge		✓
T8 - Forced Discharge, only valid for cells. See check point 1a and 9a.		✓

LITHIUM BATTERY

in accordance with manual of tests and criteria 7. revised edition, amendment 1, subsection 38.3.5

Name/Description of battery (taken from field 1)
SBP4.0

9a.UN 38.3 Test Confirmation for the Cells inside the battery When no separate document for the cells is provided, this confirms that the cells inside the battery (see checkpoint 1.a.) have successfully passed the UN 38.3 test. In this case under checkpoint 9 the T.6 and T.8 must be marked as "passed" and here under 9.a. "Cell UN 38.3 Test confirmed" needs to be ticked.	NITTE A
10. Reference to assembled battery testing requirements	
	N/A ✓
11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendment	ents thereto
ADDITIONAL SUPPLIER INQUIRY 12. Quality management system for manufacturing batteries	
Does the manufacturer of the battery manufacture the products based on a documented quality management system according to transport regulations?	YES NO
13. Are the following parameters exceeded? Lithium ion battery: more than 100 Wh Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh	YES NO
Check point 14 – 16 need to be answered when 13 has been ticked "YES":	
14. Does each battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?	YES NO
15. Is each battery equipped with an effective means of preventing external short circuits?	YES NO
16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?	YES NO

in accordance with manual of tests and criteria 7. revised edition, amendment 1, subsection 38.3.5

Name/Description of battery (taken from field 1)
SBP4.0

BATTERIES INSTALLED IN EQUIPMENT

17. Check point 17 needs t	to be answered when the batteries are installed in articles:			
17.a) Only button cells enclosed?				
17.b) Number of enclosed batteries per equipment				
When the equipment is in	tentionally active/switched on during transport e.g. data loggers:			
17.c) Confirmation that no dangerous amount of heat is emitted from the equipment N/A YES				
17.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160				
18. Place, Date	19. Name and title of the responsible person			
Ichenhausen, 27.02.2024	Pecher Andreas, Team Leader Project Management			