

Declaration of performance DoP-Nr.: D56:24-387

1. Product system	Wood(pine) D56 profile with 24mm IGU
2. Application	Outward opening windows, fixed frame windows, balcony and entrance doors for intended use or uses for commercial and private buildings (except critical zones)
3. Manufacturer	UAB "RODA", registration number 158828449 Gireles str. 20, LT-56160, Kaisiadorys, Lithuania
4. Performance assessment system	3
5. Conformity standard	EN-14351-1:2006+A2:2016
6. Notified testing authority	KTU Institute of architecture and constructions (Notified body number:2018)

This declaration of conformity is issued under the sole responsibility of the manufacturer. Product in the table below are accordance with EN 14351-1:2006+A2:2016 standard and verified by assessment of the notified body.

Air permeability (EN12207)	4
Water tightness (EN12208)	AE1100
Wind resistance (EN12210)	C3
Thermal transmittance U_w (EN ISO 10077-1& EN ISO 10077-2) W/m^2K	1,5
Light transmission T_L , % (EN410)	75
Solar energy transmission g , % (EN410)	37
Acoustic performance (EN ISO 140-1:199+A1:2004), R_w (C; C_{tr}) dB	33(-1;-5)
Load-bearing capacity of safety device	Passed*
	*- Test performed on top-turn 180° window where sash dimensions 1207*1506mm
Dangerous substances	None

Thermal transmittance U_w by positions, W/m^2K :

Pos.	Type	Height x Witdh mm	U_w W/m^2K
D110)	0200100336973>VR1-1 VU	2115 x 880	1.44
L25)	7340123300629>T1	1300 x 588	1.55
L54)	7340123300674>K1-2 spec	2115 x 440	1.64

DV56)	7340123300698>O1-2HI	2115 x 948	1.52
-------	----------------------	------------	------

On behalf of manufacturer signed by:

Paulius Monkevičius

COO

UAB „RODA“

LT-56160, Kaišiadorys

2024 06 17

