

Nelson

Tuft gauge	1/4 loop pile		ISO 2424
Pilecomposition	100% Wool		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	AB, Felt		ISO 2424
Width	400 cm, 500 cm	± 1%	EN 984
Pile Weight	1000 gr/m ²		ISO 8543
Total weight	AB : 1800 gr/m ² Felt : 1850 gr/m ²	± 15%	ISO 8543
Pile height	5 mm	± 2 mm	ISO 1766
Total Height	AB : 7 mm Felt : 9 mm		ISO 1765
Number of knots	43175/m ²	-7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1	EN 13501-1	
Use Area	Heavy domestic use (23)		EN 1307
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01

Floorsymbols



Certificates



2013

Condor Carpets
Euroweg 3
8061 SB Hasselt

EN1307

DOP: C-027AN095

Reaction to fire:
Cfl-s1
1658

Slip resistance: DS

AB

Resilient floor
covering to be
used within a
building



2013

Condor Carpets
Euroweg 3
8061 SB Hasselt

EN1307

DOP: C-027FN095

Reaction to fire:
Cfl-s1
1658

Slip resistance: DS

Felt

Resilient floor
covering to be
used within a
building

