

GRABO PRO-LIFTER 20

HEAVY LIFTING MADE EASY









Specifications:

| Model/SKU | GRABO PRO-LIFTER 20 / GP-1Li-FB | | | | |
|-------------------------------------|---|--|--|--|--|
| Battery | 14.8VDC 2600mAh Li-ion | | | | |
| Rated Power | 16W | | | | |
| Charger Input Voltage | 100-240VAC 50/60Hz | | | | |
| Battery Charging Time | ~2hrs | | | | |
| Non-Stop Running Time (Full Charge) | 1.5hrs | | | | |
| Stand-by Mode (Charge Hold) | 30 days | | | | |
| Pump Service interval | 800+ hrs continuous | | | | |
| Rated Air Flow | 0.7cfm (20 L/min) | | | | |
| Maximum Vacuum Rate | 11.6Psi (0.8 Bar, 80 kPa) | | | | |
| Maximum Lifting Capacity | 120 kg | | | | |
| LxWxH | 300 x 184 x 121 mm | | | | |
| Net Weight (With Battery) | 1.5 kg | | | | |
| Working Temperature | 0°~60 °C | | | | |
| Applicable Surface Type | Peak/valley heights less than 0.1" (3mm), arc less than 5° | | | | |
| Additional Features | Pump stops automatically at maximum vacuum rate (11.6Psi / 0.8 Bar) | | | | |

Lifting Capacity:

| Material Direction | Glass | Ceramic Tiles | Metal | Plastic | Wood | Rough Slate | Rough Concrete | Dry Wall |
|-----------------------|--------|------------------|--------|---------|--------|----------------|-------------------|-------------|
| Perpendicular Hold | 170 kg | 170kg | 110 kg | 100 kg | 100 kg | 80 kg | 80 kg | 75 kg |
| Parallel Hold | 120 kg | 120 kg | 110 kg | 100 kg | 65 kg | 80 kg | 80 kg | 65 kg |

Based on product information at time of publication. Environmental conditions can affect product performance and longevity; consult the product manual on GRABO.com or contact a Sales Representative for more information.



OM SA L



