



### PRODUCT DESCRIPTION

Dimensions	504mm x 84mm		
Thickness	8mm		
Bevels	4		
Loc System	Chateau Loc - Type A and Type B		
Classification of use	Class 23/32 According to European Standard EN13329		

	Contains	m <sup>2</sup>	ft <sup>2</sup>	Weight
1 pack	24 planks	1,02 m <sup>2</sup>	10,94 ft <sup>2</sup>	7,3 kg
1 pallet	48 packs	48,77 m <sup>2</sup>	524,97 ft <sup>2</sup>	365 kg

### COMPOSITION

Surface layer	Direct laminated paper, impregnated with melamine resin
Substrate	Moisture resistant High Density Fiberboard (HDF)
Backing	Direct laminated paper, impregnated with melamine resin

### TESTED VALUE

Abrasion resistance	EN13329	AC4 (IP≥4000)
Impact resistance	EN13329	Small ball : ≥ 12 N - Big ball : ≥ 750 mm
Thickness swelling	EN13329	12% (requirement ≤ 18%)
Fire resistance	EN14041	Cfl-S1
Formaldehyde	EN14041	E1
Slipperiness	EN14041	DS
Density	EN323	900 kg
Resistance to staining	EN438	5 (groups 1+2); 4 (group 3)
Resistance to cigarette burns	EN438	4
Effect of a furniture leg	EN424	No damage (foot type 0)
Effect of a castor chair	EN425	No change in appearance or damage
Thermal resistance in combination with underlay Excellence Plus		0,08 m <sup>2</sup> K/W – Suitable for floor heating/cooling. Detailed instructions on <a href="http://www.berryalloc.com">www.berryalloc.com</a>

### METHOD

### TEST RESULTS

### CERTIFICATES/LABELS

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+
- DOP : 170-DPLA18-1

### WARRANTY

- Lifetime Residential Warranty
- 5 Years of Commercial Warranty
- Warranty conditions on [www.berryalloc.com](http://www.berryalloc.com)

