

Type	57976
Designation	Power Bank Energy
Systems to charge	Lithium-Polymer / 3.7 V / 1 pcs.
Cell configurations	2x 5000 mAh, 37.0 Wh
Housing Material	ABS
Dimensions	Charger:
Length.....	138 +- 1 mm
Width.....	73 +- 1 mm
Height	15 +- 1mm
Weight.....	233 g +- 5g



Charging methods:	Plug in Micro USB and USB Type C port:	Maintenance Charge:
Input 1: Micro USB	Current: 500 mA - 3000 mA	N/A
Input 2: USB Type C.....	Current: 3000 mA	
Discharging methods:	USB A and Type C port for charging other devices:	
Output 1 & 2 USB A.....	5.0 V, 2400 mA	
Output 3 USB Type C.....	5.0 V, 3000mA	
Rated Capacity	5920mAh @ 5V / 1A / USB A	

Indications for IN:			
4 LEDs	100%	Capacity	} LEDs on LEDs indicate level of charge and next level is flashing
3 LEDs	75 - 99%	Capacity	
2 LEDs	50 - 75%	Capacity	
1 LED.....	25 - 50%	Capacity	
LED off.....	< 25%	Capacity	

Indications for OUT:		
4 LEDs	75 - 100 %	Capacity
3 LEDs	50 - 75 %	Capacity
2 LEDs	25 - 50 %	Capacity
1 LED.....	10 - 25 %	Capacity
LED blinking	< 10 %	Capacity

Ambient temperature:	
Charge	0 - +45 °C
Discharge	-10 - +55 °C
Storage (short time).....	-10 - +60 °C
Storage (long time).....	+10 - +35 °C

Cut off criteria:	
Li-Ion cells.....	Stop discharging, when Li-Ion voltage lower than 2.8 V Short circuit protection Overload protection NTC temperature protection

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries