












## TECHNICAL INFORMATION / TEKNISK INFORMATION



# BERGO XL

|  |   |                                    |  |   |
|--|---|------------------------------------|--|---|
| Material:                                    |    | ISO2076                            | Environmentally friendly recyclable UV-stabilized polypropylene.   | / Miljövämlig återvinningsbar UV-stabiliserad polypropen. |
| Size of tile:<br>/Plattans storlek:          |    | EN427                              | 377,2 x 377,2 mm. 1 m <sup>2</sup> / box = 7 tiles.<br>5 m <sup>2</sup> / box = 35 tiles.                    |   |
| Thickness of tile:<br>/Plattans tjocklek:    |    | EN428                              | 10,1 mm.   |   |
| Weight:<br>/Vikt:                            |    | EN430                              | 1 tile: 0,350 kg.<br>1 m <sup>2</sup> : 2,63 kg (Consumer pack).<br>5 m <sup>2</sup> : 12,85 kg (Maxi-pack). |   |
| Point load:<br>/Punktbelastning:             |    | QUALIFIED TEST<br>BY BERGO         | 250 ton / 1 m <sup>2</sup> = 2500 kg/dm <sup>2</sup>   |   |
| Light fastness:<br>/Ljusbeständighet:        |    | EN 14836 (>3)<br>ISO 105-B02 (1-8) | 4-5<br>7-8   |   |
| Weather Fastness /UV-<br>Florida test (1-5): |   | ASTM D1435<br>ASTM G154 Cycle A    | 4/5  |   |
| Slip resistance:<br>/Halkmotstånd:           |  | SSEN-13893                         | >0,3   |   |
| Impact resistance:<br>/Slagtålighet:         |  | ISO179/1eA<br>ASTM D746            | +23 °C = 20 kJ/m <sup>2</sup> / -20 °C = 5 kJ/m <sup>2</sup><br>C15 kJ/m <sup>2</sup>                        |   |
| Fire category<br>/Brandklassning:            |  | EN ISO 11925-2                     | E <sub>fl</sub>  |   |
| CE certification:                            |  | EN 14041                           | 0402-CPD-P605080A  |   |

| Packaging:    | Quantity / packaging unit:  | Quantity / pallet:                         | Size of pallet:  |
|---------------|-----------------------------|--|--|
| Consumer-pack | 1 m <sup>2</sup> = 7 tiles  | 1 pallet = 90 cartons = 90 m <sup>2</sup>  | 1,20 x 0,80 x 1,23 m = 1,18 m <sup>3</sup> , 262 kg gross weight |
| Maxi-pack     | 5 m <sup>2</sup> = 35 tiles | 1 pallet = 36 cartons = 180 m <sup>2</sup> | 1,20 x 0,80 x 2,41 m = 2,31 m <sup>3</sup> , 480 kg gross weight |




By normal use and treatment the material guarantee time is 10 years.



Bergo Flooring AB fulfills the requirements of ISO 9001.



Bergo Floors are 100% recyclable.



www.bergoflooring.com

