

## Sweet

<b>Tuft gauge</b>	5/32 cut pile		ISO 2424
<b>Pilecomposition</b>	100% PES		ISO 2424
<b>Primary Backing</b>	Woven		ISO 2424
<b>Secondary backing</b>	Duo Backing, Felt		ISO 2424
<b>Width</b>	400 cm	± 1%	EN 984
<b>Pile Weight</b>	1100 gr/m <sup>2</sup>		ISO 8543
<b>Total weight</b>	Felt : 1950 gr/m <sup>2</sup> Duo Backing : 1900 gr/m <sup>2</sup>	± 15%	ISO 8543
<b>Pile height</b>	12 mm	± 2 mm	ISO 1766
<b>Total Height</b>	Felt : 15 mm Duo Backing : 14 mm		ISO 1765
<b>Number of knots</b>	68.040/m <sup>2</sup>	-7.5% .+10%	ISO 1763
<b>Fire Classification</b>	Cfl-S1	EN 13501-1	
<b>Use Area</b>	Heavy domestic use (23)		EN 1307
<b>GUT Nr.</b>	7CBEA0FD GUT		www.pro-dis.info
<b>Thermal resistance</b>	Ca. 0.08 M <sup>2</sup> KW		ISO 8302
<b>Light fastness</b>	≥ 5		105-B02
<b>Wearebility</b>	≥ 4		105-X12
<b>Water fastness</b>	≥ 4		105-E01

## Floorsymbols



## Certificates



2019

Condor Carpets  
Euroweg 3  
8061 SB Hasselt

EN1307

DOP: C-025FS337

Reaction to fire:  
Cfl-s1  
1688

Slip resistance: DS

Resilient floor  
covering to be  
used within a  
building



**Intenza**  
the ultimate in soft carpets

